

Amplifiers

VHF/UHF PREAMPLIFIER



7415L



- FM input/B.III or DAB input/UHF input
- 1 wideband output
- 12 dB gain on FM
- 15-30 dB adjustable gain on B.III/DAB
- 20-35 dB adjustable gain on UHF
- LTE (4G)
- low-noise
- 24 VDC operating voltage
- wall or mast mountable

7415L

	-	BII (FM)	BIII/DAB	UHF C21-60
Inputs	-	BII (FM)	BIII/DAB	UHF C21-60
Frequency range	MHz	88-108	170-240	470-790
Gain	dB	12	15-30	33-20
Noise Figure	dB	4	2,0	3,2
Max. input level	dBµV	99	91	84
Max. Output level	dBµV	111	107	108
Power supply	VDC	24		
Consumption	mA	60		
Dimensions	mm	112 x 98 56 mm		



7460



- 1 x VHF input/1 x UHF input
- 1 wideband output
- up to 105 dBµV output power
- 5-20 dB adjustable gain on VHF
- 20-35 dB adjustable gain on UHF
- LTE (4G)
- low-noise
- power indication LED
- 24 VDC operating voltage

7460

	-	VHF (BIII/DAB)	UHF (Ch. 21-60)
Inputs	-	VHF (BIII/DAB)	UHF (Ch. 21-60)
Frequency range	MHz	170-240	470-790
Gain	dB	5-20	20-35
Noise Figure	dB	4,2	2,5
Max. input level	dBµV	107	85
Max. Output level	dBµV	107	103
Power supply	VDC	24	
Consumption	mA	35	
Dimensions	mm	120 x 115 x 50	

► For other products within this category see p.105.