

## antenne paraboliche / satellite antennas

### parabole offset / offset parabolic dishes



- Antenne paraboliche di tipo offset realizzate mediante un procedimento di stampaggio ad alta precisione che garantisce una costante qualità di produzione.
- Riflettore in lamiera di acciaio zincato oppure in lega di alluminio.
- Verniciatura realizzata a polveri per esterni in 3 colori: bianco, grigio scuro e rosso mattone.
- Tutti i modelli forniti con supporto fisso Az-El portano incisa la scala di regolazione dell'alzo.
- Per segnali deboli, per sistemi centralizzati o per impianti multi-satellite, si consigliano i modelli Ø 85, 100, 115, 125, e 150 cm offset e i relativi accessori.

Brevetti Emme Esse

- *Offset parabolic dishes realized by high precision forming which guarantees a constant production quality.*
- *Dishes can be either in hot-galvanized steel sheet or in varnished aluminum sheet.*
- *Dense paint finishing available in 3 colors: standard (white), dark grey, brick-like red.*
- *All models supplied with fixed Az-El mount with zenith indicator.*
- *For weak signals, for centralized systems or for multi-satellite installations dishes Ø 85, 100, 115, 125 and 150 cm are recommended with their own accessories.*

Patents Emme Esse

codice code	diametro diameter Ø	materiale material	guadagno a 12Ghz gain dB	fissaggio al palo mast fixing Ø mm	fissaggio lnb lnb fixing Ø mm	alzo massimo max elevation deg
8045A	45	acciaio/steel	33,0	28 ... 50	23 - 40	18° - 52°
8045	45	alluminio/alu	33,0	28 ... 50	23 - 40	18° - 52°
8060A	60	acciaio/steel	36,0	30 ... 60	23 - 40	15° - 60°
8060	60	alluminio/alu	36,0	30 ... 60	23 - 40	15° - 60°
8065A	65	acciaio/steel	36,6	30 ... 60	23 - 40	15° - 60°
8065	65	alluminio/alu	36,6	30 ... 60	23 - 40	15° - 60°
8080A	80	acciaio/steel	38,8	30 ... 60	23 - 40	15° - 60°
8080	80	alluminio/alu	38,8	30 ... 60	23 - 40	15° - 60°
8085A	85	acciaio/steel	39,5	30 ... 60	23 - 40	15° - 52°
8085	85	alluminio/alu	39,5	30 ... 60	23 - 40	15° - 52°
80100A	100	acciaio/steel	40,3	30 ... 60	23 - 40	15° - 57°
80100	100	alluminio/alu	40,3	30 ... 60	23 - 40	15° - 57°
80115A	115	acciaio/steel	41,6	30 ... 60	40	15° - 57°
80115	115	alluminio/alu	41,6	30 ... 60	40	15° - 57°
80125	125	alluminio/alu	42,5	30 ... 70	40	21° - 66°
80015	150	alluminio/alu	43,5	60 ... 90	40	15° - 90°

#### NOTE

Colore standard bianco, imballo singolo  
Per variante colore aggiungere: G per Grigio scuro, R per rosso. Per imballo industriale aggiungere: S per 12 pz, SC per 50 pz  
Es: 8080AGS Grigio – imballo 12 pz  
8085RSC Rosso – imballo 50 pz

#### NOTE:

Standard white colour, single packaging  
For other colour add: G for Grey, R for Red  
For bulk packaging add: S for 12 pcs, SC for 50 pcs  
Ex: 8080AGS Grey – bulk 12 pcs  
8085RSC Red – bulk 50 pcs

## antenne paraboliche / satellite antennas

## parabole offset / offset parabolic dishes

- Carpenteria realizzata in lamiera d'acciaio zincata a caldo.
- Monopode in lega di alluminio.
- Il portafeed può montare LNB con diametro 23 o 40 mm (ad eccezione delle parabole Ø 115, 125 e 150 che hanno un attacco solo per LNB con diametro 40 mm).

- *Hot-galvanized steel sheet mounts.*
- *Feed-arm in aluminum alloy.*
- *The feed-holder can mount LNB with Ø 23 or 40 mm (with the exception of dishes Ø 115, 125 and 150 which only mount LNB with Ø 40 mm).*



Carpenteria / mounts Ø 60-65



Carpenteria / mounts Ø 80



Carpenteria / mounts Ø 85



Carpenteria / mounts Ø 100



Carpenteria / mounts Ø 115



Carpenteria / mounts Ø 125




Carpenteria / mounts Ø 150

Supporto in polipropilene  
PP support with fiber glass Ø 45


01



02



03



01  
Sistema di apertura pre-montato. Brevetti Emme Esse.  
*Pre-mounted opening system. Patents by Emme Esse.*

02  
Montaggio rapido con cavallotto  
*Fast mounting with U-bolt*

03  
Portafeed con viti premontate  
*Feed holder with pre-mounted screws*